AMENDMENTS

In The Claims:

Please amend the claims as follows.

1.-22 (cancelled).

23. (Previously presented) A communication system comprising:

(a) a hub for communicating at least one first signal and at least one second signal, converting the first signal into a radio frequency with an appropriate format and transmitting the first signal to conductive elements via an exciter;

(b) a probe for receiving the first signal, converting the first signal into the second signal and transmitting the second signal to the hub via the exciter;

wherein the conductive elements are conductive members selected from a conductive frameworks, electrical wires, metal walls or any combination thereof; and

the conductive elements receive the second signal from the probe and transmit the second signal to the exciter.

24. (Currently amended) The system recited in claim [~~1~~] 23, wherein the hub includes at least one of a diplexer, a power amplifier, a transmitter, a receiver, a frequency converter, a modem, a security controller, and a network processor.

25. (Currently amended) The system recited in claim [~~2~~] 24, wherein the security controller processes signals from a camera or another hub comprising a receiver and a transmitter.

26. (Currently amended) The system recited in claim [~~1~~] 23, wherein at least one of the first signal and the second signal are at a radio frequency between 0.5-100 MHz.

27. (Currently amended) The system recited in claim [~~1~~] 23, wherein at least one of the first signal and the second signal includes information from at least one of a satellite television, a cable television, an Internet provider, a computing device, a phone provider, a DVD player, a computer, a television, DSL, and LAN.

28. (Currently amended) The system recited in claim [~~1~~] 23, wherein the hub is connected to another hub by a hard wire or wirelessly.

29. (Currently amended) A communication method comprising the steps of:

(a) communicating at least one first signal and at least one second signal, converting the first signal into a radio frequency with an appropriate format and transmitting the first signal to conductive elements via an exciter by a hub;

(b) allowing a probe to receiving the first signal, to convert the first signal into the second signal and to transmit the second signal to the hub via the exciter;

wherein the conductive elements are conductive members selected from a set including conductive frameworks, electrical wires, metal walls or any combination thereof; and

the conductive elements receive the second signal from the [~~prove~~] probe and transmit the second signal to the exciter.

30. (Currently amended) The method recited in claim [~~7~~] 29, wherein the hub includes at least one of a diplexer, a power amplifier, a transmitter, a receiver, a frequency converter, a modem, a security controller, and a network processor.

31. (Currently amended) The method recited in claim [~~8~~] 30, wherein the security controller processes signals from a camera or another hub comprising a receiver and a transmitter.

32. (Currently amended) The method recited in claim [~~7~~] 29, wherein at least one of the first signal and the second signal is at a radio frequency between 0.5-100 MHz.

33. (Currently amended) The method recited in claim [~~7~~] 29, wherein at least one of the first signal and the second signal includes information from at least one of a satellite television, a cable television, an Internet provider, a computing device, a phone provider, a DVD player, a computer, a television, DSL, and LAN.

34. (Currently amended) The method recited in claim [~~7~~] 29, wherein the hub is connected to another hub by a hard wire or wirelessly.

35. (Currently amended) A hub [~~utilizing~~] utilized for a communication system,

wherein the hub for communicating at least one first signal and at least one second signal, converting the first signal into a radio frequency with an appropriate format and transmitting the first signal to conductive elements via an exciter;

wherein the communication system includes a probe for receiving the first signal, converting the first signal into the second signal and transmitting the second signal to the hub via the exciter;

wherein the conductive elements are conductive members selected from a set including conductive frameworks, electrical wires, metal walls or any combination thereof; and

the conductive elements receive the second signal from the [~~probe~~] probe and transmit the second signal to the exciter.

36. (Currently amended) The hub recited in claim [~~13~~] 35, wherein the hub includes at least one of a diplexer, a power amplifier, a transmitter, a receiver, a frequency converter, a modem, a security controller, and a network processor.

37. (Currently amended) The hub recited in claim [~~14~~] 36, wherein the security controller processes signals from a camera or another hub comprising a receiver and a transmitter.

38. (Currently amended) The hub recited in claim [~~13~~] 35, wherein at least one of the first signal and the second signal is at a radio frequency between 0.5-100 MHz.

39. (Currently amended) The hub recited in claim [~~13~~] 35, wherein at least one of the first signal and the second signal includes information from at least one of a satellite television, a cable television, an Internet provider, a computing device, a phone provider, a DVD player, a computer, a television, DSL, and LAN.

40. (Currently amended) The hub recited in claim [~~13~~] 35, wherein the hub is connected to another hub by a hard wire or wirelessly.